



MATERIALS:
 HEAT SINK:AL
 CONNECTOR: Cu
 SUBSTRATE: ALUMINUM NITRIDE
FINSH:
 HEAT SINK: OXIDATION
 CONNECTOR: ALLOY PLATED ON
 COPPER BODY
TECHNICAL:
 FREQUENCY RANGE(GHz):DC-3.0
 OPERATING TEMPERATURE(°C):-55°
 TO+125°
 AVERAGE POWER(WATTS):10
 VSWR: 1.20MAXIMUM
 RESISTANCE RANGE: 50 OHMS
 CONNECTOR: N TYPE
 ATTENUATION:3,6,10,15,20,30DB
 AVAILABLE,AND1-10dB
 ±0.5DB,15-30DB±1DB

				TOLERANCES				RF POWER CENTRON MICROWAVE COMPONENT (SHENZHEN) CO., LTD.			
				,X± 0.1				NAME	10W ATTENUATORS	NO.	MANA10N
				,XX± 0.01 ANGLES X° ±0.1				DRAWING NO	2009050201	DRAWN	XIE XIANG LONG
				,XXX ±0.001							
REV	DESCRIPTION	DRAWN	APVD	SCALE		REV	A	CHKD		DATE	15.MAY.2009
				SHEET OF							