


MATERIALS:
 HEAT SINK:AL
 CONNECTOR: Cu
 SUBSTRATE: ALUMINUM NITRIDE
FINISH:
 HEAT SINK: OXIDATION
 CONNECTOR: ALLOY PLATED ON
 COPPER BODY
TECHNICAL:
 FREQUENCY RANGE(GHz):DC-3.0
 OPERATING TEMPERATURE(°C):-55°
 TO+125°
 AVERAGE POWER(WATTS):5
 VSWR: 1.20MAXIMUM
 RESISTANCE RANGE: 50 OHMS
 CONNECTOR: N TYPE
 ATTENUATION:3,6,10,15,20,30DB
 AVAILABLE,AND1-10dB
 ±0.5DB,15-30DB±1DB

				TOLERANCES				 CENTRON MICROWAVE COMPONENT (SHENZHEN) CO. , LTD.			
				,X± 0.1 ,XX± 0.01 ANGLES X° ±0.1 ,XXX ±0.001				NAME	5W ATTENUATORS	NO.	MANA5N
				SCALE		REV	A	DRAWING NO		DRAWN	XIE XIANG LONG
REV	DESCRIPTION	DRAWN	APVD	SHEET OF				CHKD		DATE	15.MAY.2009