


MATERIALS:
 HEAT SINK:AL
 CONNECTOR: Cu
 SUBSTRATE: ALUMINUM NITRIDE

FINSH:
 HEAT SINK: OXIDATION
 CONNECTOR: ALLOY PLATED
 ON COPPER BODY

TECHNICAL:
 FREQUENCY RANGE(GHz):DC-3.0
 OPERATING TEMPERATURE(°C):
 -55° TO+125°
 AVERAGE POWER(WATTS):25
 VSWR: 1.20MAXIMUM
 RESISTANCE RANGE: 50 OHMS
 CONNECTOR: N TYPE

| | | | | TOLERANCES | | | |  CENTRON MICROWAVE COMPONENT (SHENZHEN) CO., LTD. | | | |
|-----|-------------|-------|------|---|--|-----|---|---|--------------------|-------|----------------|
| | | | | ,X± 0.1 ,XX± 0.01 ANGLES X° ±0.1 ,XXX ±0.001 | | | | NAME | 25W TERMINATION | NO. | MANT25N |
| | | | | SCALE | | REV | A | DRAWING NO | | DRAWN | XIE XIANG LONG |
| REV | DESCRIPTION | DRAWN | APVD | SHEET OF | | | | CHKD | | DATE | 15.MAY.2009 |